



## BV-C1060H

### 1/3 inch NTSC/PAL color video camera



BV-C1060H employs 1/3 inch 480K pixels (NTSC) or 570K pixels (PAL) CCD and provides high sensitive and high S/N pictures.

Item	Specifications (NTSC)	Specifications (PAL)
Image sensor	1/3-inch CCD	
Total pixel numbers	976(H) x 494(V)	976(H) x 582(V)
Scan system	Interlace	
Synchronization	Internal	
Horizontal frequency	15.734KHz	15.625KHz
Vertical frequency	59.94Hz	50Hz
Video output	Analog: Composite 1Vp-p 75Ω	
Horizontal resolution	680 TV lines (Luminance signal)	
Minimum illumination	0.1Lx (AGC ON, F1.4, Output:25IRE)	
S/N	52dB (Typical) (AGC off, Weight ON)	
Gamma correction	0.45, 1.0(OFF)	
AGC	Analog: 36dB, Digital: 24dB	
Iris control	DC control	
Auto shutter	1/60 ~ 1/120,000	1/50 ~ 1/120,000
Interface	Serial interface	
On screen display	Equipped on rear panel	
Lens mount	C mount	
Input voltage	DC 12V	
Power consumption	3.4W	
Operating temperature / Humidity	-10°C to + 50°C / 80% (Non-condensing)	
保存温度/ 湿度	-30°C to + 70°C / 80% (Non-condensing)	
Dimensions (WxHxD)	55 x 55 x 51mm (excluding protrusion)	
Weight	220g	

■ Specifications are subject to change without notice