



BV-C3100 SWIR Line Scan Camera

BV-C3100 is an exclusive NIR line scan camera with sensor having the sensitivity from 950nm to 1700nm.



BV-C3100 uses a sensor having 25 micron pixel size and sensitivity from 950nm to 1700nm. The interface used is Camera Link Base Configuration and lens mount can be selected from C mount or M52 mount.

M52 mount type: BV-C3100-M

C mount type: BV-C3100-C (photo)

Item	Specifications
Line Sensor	Effective Pixel: 512pixels, Pixel size: 25μm x 25μm, Effective image length: 12.8mm x 1 Anti-Ghost type InGaAs sensor is employed
Wave length	950nm ~ 1700nm
Synchronization	Internal, External trigger
Pixel clock cycle	200ns ~ 10μs (Setting is 12.5ns/step)
Line rate	123.2μs (Pixel clock period: 200ns, at Shutter time: 17.8μs)
Line frequency	8.117KHz (Pixel clock period: 200ns, at Shutter time: 17.8μs)
Sensor Conversion Efficiency	0.93μV/e ⁻
S/N	55dB (Gain=0dB)
Electronic shutter	Range: 17.8μs ~ 100ms (Setting Unit: 12.5ns)
Gain	0dB ~ +24dB (x1 ~ x16, 1/16 step)
Black level	-127 ~ 127LSB (10bit output)
Blemish Compensation	Black defect : ON/OFF
Shading Compensation	Flat Shading Compensation
Video Output	Camera Link 10 bit Base Configuration x 1
Operating mode	Shutter mode (Internal, External trigger)
Trigger input	Hirose12P: TTL(Max. voltage: Power voltage), Camera Link: LVDS(CC1,CC2)
Sync output	XEEN(Hirose12P), LVAL,DVAL,EEN(Camera Link)
Communication interface	Camera Link: EIA644 9600bps,115200bps selectable
Lens mount	M52 mount: Flange back 46.5mm - 0.05mm or C mount: Flange back 17.526mm - 0.05mm
Power supply	DC12V ± 10%
Operating Ambient Temperature	-5°C ~ +45°C / 20% ~ 80% (no condensing)
Dimensions (WxHxD)	95 x 95 x 95mm (excluding protrusion)
Weight	820g

Associated product: Lens for BV-C3100-M (BV-L1020-SWIR, BV-L1024-SWIR, BV-L1028-SWIR, BV-L1035-SWIR, BV-L1050-SWIR, BV-L1105-SWIR)

Lens for BV-C3100-C (BV-L1020-SWIR-C, BV-L1024-SWIR-C, BV-L1028-SWIR-C, BV-L1035-SWIR-C, BV-L1050-SWIR-C, BV-L1105-SWIR-C)

- Specifications are subject to change without notice
- This product is in the scope of Export Trade Control Order and requires Export License etc.

Bluevision Ltd., Japan

1-13-12 Shin-Yokohama, Kohoku-ku, Yokohama 222-0033

TEL: 045-471-4595 FAX: 045-471-4598

URL: www.bluevision.jp

Contact: sales@bluevision.jp